

## Product Data Sheet – EZ Pave

**Product Name:** EZ Pave

**Product Type:** Biodegradable Asphalt Release Agent

**Manufacturer:** Bio Green Industrial INC

**Origin:** Made in Canada

**Availability:** Sold throughout North America

---

### Appearance & Physical Properties:

- **Appearance:** Light amber liquid
- **Specific Gravity:** ~0.8-0.9
- **Bulk Density:** 0.8-0.9 kg/L (6.7-7.5 lbs per US gallon)
- **V.O.C.:** Low 0.07 - 0.08 g/L

EZ Pave D6751 appears as a light amber liquid with a low, oily odor and is formulated to prevent asphalt from adhering to truck beds, tools, and machinery.

---

### Ordering, Handling & Protection:

EZ Pave D6751 is available in:

- **205-litre lined drums**
- **18.93-litre plastic spouted pails**
- **Bulk deliveries** to approved customer facilities or in **Bio Green Industrial tote tanks 1000 litres**

### Safety Precautions:

- Avoid eye contact; use eye protection.
- Wash eyes with warm water if exposed.
- Harmful if swallowed; seek medical assistance if ingestion occurs.
- Keep out of reach of children.

### Company Address:

Bio Green Industrial INC

45540 Sunnyside Mall, Surrey BC, Canada

Telephone: 1(604) 816-1136

---

## Installation Instructions:

### Preparatory Work:

1. Surfaces should be **clean and free from dirt, oil, and asphalt buildup**.
2. Surfaces should be **dry** before application.
3. Apply one or two **heavy brush coats** to high-exposure areas to enhance protection.

### Application Instructions:

1. **EZ Pave D6751 is ready to use** and can be applied by **brush, roller, or low-pressure sprayer**. Stir before each use.
2. Apply at the coverage rate specified below.
  - 3a. **Brush Application:** Apply evenly with a soft bristle brush.
  - 3b. **Roller Application:** Apply with full, even strokes ensuring no pinholes or uncoated areas.
  - 3c. **Sprayer Application:** Use a **low-pressure sprayer**, ensuring even coverage without overspray.

### Rate of Application:

- **Steel truck beds:** 20m<sup>2</sup> per litre (600 sq. ft. per US gallon)
- **Rubberized surfaces:** 15m<sup>2</sup> per litre (450 sq. ft. per US gallon)
- **Equipment & tools:** 18-22m<sup>2</sup> per litre (500-700 sq. ft. per US gallon)

---

## Environmental & Safety Benefits:

- ✓ **Non-Hazardous & Biodegradable**
- ✓ **Safe Alternative to Petroleum-Based Release Agents**
- ✓ **Minimal Ecotoxicity & No Soil or Water Accumulation**
- ✓ **Complies with OSHA (29 CFR 1910.1200) & WHMIS 2015 Regulations**

---

For more information, contact **Bio Green Industrial INC** at **1(604) 816-1136** or visit our website. **[www.biogreenindustrial.com](http://www.biogreenindustrial.com)**